

# Manual Call Points

## Extinguishing Agent Release

### General

Notifier extinguishing agent release Manual Call Points (MCP's) are designed to be used as a component of a fire suppression system.

These MCP's come in three variants; indoor flush or surface mount and a weatherproof version for use outdoors or in areas where moisture or dust are present.

### Features

- Sealed to IP24, weatherproof versions to IP67.
- Indoor versions suitable for flush mounting or surface mounting.
- Anti-tamper facility.
- Enhanced aesthetics and compact design.
- Unique 'Plug & Play' installation concept.
- Total 'Flex-Ability' in the choice of operating element.



**Flush Mount**



**Surface Mount**



**Weatherproof**

## Specification

Maximum Voltage:	30VDC
Switch Rating:	2A
LED Rating:	Max. 30mA
Temperature Range:	-10°C to 55°C
Humidity Range:	0% to 95% non-condensing
IP Rating:	IP67
EOL Value:	47K ohms.

## Ordering Information

<b>FG-18-012</b>	MCP-3A-YFG "Extinguishant Release" Manual Call Point - Yellow -Flush mount
<b>FG-18-013</b>	MCP-3A-YSG "Extinguishant Release" Manual Call Point - Yellow -Surface mount
<b>FG-18-014</b>	WCP-3A-YSG "Extinguishant Release" Weatherproof Manual Call Point - Yellow -Surface mount
<b>FG-18-019</b>	Spare Glass for all MCP's
<b>FG-18-021</b>	Spare flap for all KAC MCP's
<b>FG-18-022</b>	Re-settable element for all KAC MCP's
<b>FG-18-023</b>	Spare test key for all MCP's

---

© 2009 by Honeywell International Inc. All rights reserved.  
Unauthorised use of this document is strictly prohibited.

---

This document is not intended for installation purposes.  
We try to keep our product information up-to-date and accurate.  
We cannot cover all specific applications or anticipate all requirements.  
All specifications are subject to change without notice.

For more information contact your nearest Notifier Sales Office or Distributor  
[www.notifier.com.au](http://www.notifier.com.au)